

## NOTES:

- 1. ON MEDIANS LESS THAN 14 FEET WIDE, REPLACE MAINTENANCE BAND WITH 18 INCH MINIMUM WIDTH PLANTING OF WALKABLE GROUNDCOVER.
- 2. IF CONCRETE, INSTALL DEEP JOINTS TO MATCH CURB & GUTTER DEEP JOINTS. SEE ENGINEERING STANDARD DETAIL 8 FOR DEFINITION OF DEEP JOINT.
- 3. FOR PAVERS WITHIN THE DRIPLINE OF AN EXISTING TREE, HAND EXCAVATE ALL AREAS.
  6" CLASS 2 PERM LAYER MAY BE REDUCED OR ELIMINATED IF NECESSARY. SEE LSD-9 FOR TREE PRESERVATION NOTES.
- 4. PAVERS TO BE: 6 X 9 X 3 1/8 CALSTONE PERMEABLE PAVING UNITS, COLOR: RUSTIC YELLOW STONE, UNLESS APPROVED BY THE CITY LANDSCAPE ARCHITECT.

			CITY OF FREMONT STANDARD DETAILS CITY STANDARD				DATE APPROVED BY CITY COUNCIL 12/13/11  RESOLUTION NO. 2006-31	
MA	General Revisio	n 09/05/12					2000-	<u> </u>
	Council Revision	12/13/11					11 11 1	
APPR	REVISED	DATE				Nam Hughes		
REVISIONS			MAINTENANCE BAND				CITY ENGINEER	
FILE NO.		SCALE		DRAWN	CHECKED	DATE	DWG NO.	
L	LSD-8.DWG		: 1'-0"	PM/MM	RER	DEC. 2011	LSD-8	1 of 1